

CONTRAST RED PLUS

Description

High print quality:

Ideal printing blanket for demanding print jobs.

Excellent Ink Transfer:

The micro-buffed surface allows for sharp do reproduction and low dot gain .


Compressible Layer:

Closed cell compressible layer for minimal sinking, excellent rebound and smash resistancy.

MAIN APPLICATION

Commercial Sheetfed, Packaging, Metal Decorating

Rollin Contrast Red Plus is available in 3-ply, (1,96 mm) thickness.





Standard

Rollin Contrast Red Plus



The product at a glance

PRINTING SURFACE COLOUR	Red
THICKNESS (mm)	1,96
SURFACE ROUGHNESS (Ra micron)	0,6
INK COMPATIBILITY	Hybrid
ELONGATION (%)	<0,9
TENSILE STRENGHTS (N/mm)	>60
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
WATER SOLVENT PROTECTED	Yes
NEW TECNOLOGIES	Dynatech
ADDITIONAL INFORMATION	
HYBRID TOP FACE COMPOUND	Conventional & UV inks Print quality and durability Edge marking resistant Very special compressible layers



DISTRIBUTED BY:

OMC, sae

Tel. 902 906 980 info@omcsae.com www.omcsae.com

